

View Online at <https://aerobasegroup.com/nsn/5306-01-550-7097>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.420 inches

Fastener Length:

2.440 inches

Head Style:

Double hexagon w/hole

Head Height:

0.265 inches

Width Between Flats:

0.250 inches

Extended Washer Thickness:

0.055 inches

End Application:

1520-01-471-6743, helicopter, search and rescue

Thread Diameter:

0.190 inches

Grip Length:

2.000 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

180000 pounds per square inch

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-8503 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2, federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.