

View Online at <https://aerobasegroup.com/nsn/5306-01-552-5702>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.681 inches

**Fastener Length:**

3.243 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.798 inches and 0.818 inches

**Width Between Flats:**

Between 0.928 inches and 0.940 inches

**Extended Washer Diameter:**

Between 1.428 inches and 1.438 inches

**Extended Washer Thickness:**

Between 0.188 inches and 0.208 inches

**Hole Diameter:**

0.062 inches

**Grip Diameter:**

Between 0.873 inches and 0.874 inches

**End Application:**

1680 airplane final ssy

**Thread Diameter:**

0.875 inches

**Grip Length:**

1.562 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

14

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Product Name:**

Bplt, special-power plant, eng mount, upper

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams-qq-p-35 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0