

View Online at <https://aerobasegroup.com/nsn/5306-01-552-6099>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

2.450 inches

**Fastener Length:**

2.450 inches

**Head Style:**

Headless (setscrew)

**Hole Diameter:**

0.547 inches

**Washer Quantity:**

1

**Shank Unthreaded Hole Diameter:**

0.125 inches first hole and 0.129 inches first hole

**Thread Diameter:**

0.625 inches

**Hole Quantity:**

1

**Features Provided:**

Bushing

**Thready Qty Per Inch (tpi):**

18

**Hole Thready Qty Per Inch (tpi):**

18

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.380 inches first hole

**Hole Thread Diameter:**

0.3125 inches

**Primary Washer Outside Diameter:**

Between 0.625 inches and 0.635 inches

**Primary Washer Style:**

Flat

**Primary Washer Material Thickness:**

Between 0.503 inches and 0.508 inches

**Material:**

Steel comp 303 stand-off or steel comp 304 stand-off

**Material Specification:**

Astmb21 assn standard single material response fastener

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Astma967 assn standard single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0