## NSN 5306-01-552-6099

Assembled Washer Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-552-6099

Thread Class:
Thread Class.
2a
Thread Direction:
Right-hand
Thread Length:
2.450 inches
Fastener Length:
2.450 inches
Head Style:
Headless (setscrew)
Hole Diameter:
0.547 inches
Washer Quantity:
1
Shank Unthreaded Hole Diameter:
0.125 inches first hole and 0.129 inches first hole
Thread Diameter:
0.625 inches
Hole Quantity:
1
Features Provided:
Bushing
Thready Qty Per Inch (tpi):
18
Hole Thready Qty Per Inch (tpi):
18
Distance From Head Largest Bearing Surface To Shank Hole Center:
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> 0.380 inches first hole
0.380 inches first hole
0.380 inches first hole Hole Thread Diameter:
0.380 inches first hole Hole Thread Diameter: 0.3125 inches
0.380 inches first hole Hole Thread Diameter: 0.3125 inches Primary Washer Outside Diameter:
<ul> <li>0.380 inches first hole</li> <li>Hole Thread Diameter:</li> <li>0.3125 inches</li> <li>Primary Washer Outside Diameter:</li> <li>Between 0.625 inches and 0.635 inches</li> </ul>
<ul> <li>0.380 inches first hole</li> <li>Hole Thread Diameter:</li> <li>0.3125 inches</li> <li>Primary Washer Outside Diameter:</li> <li>Between 0.625 inches and 0.635 inches</li> <li>Primary Washer Style:</li> </ul>
0.380 inches first hole Hole Thread Diameter: 0.3125 inches Primary Washer Outside Diameter: Between 0.625 inches and 0.635 inches Primary Washer Style: Flat
0.380 inches first hole Hole Thread Diameter: 0.3125 inches Primary Washer Outside Diameter: Between 0.625 inches and 0.635 inches Primary Washer Style: Flat Primary Washer Material Thickness:
0.380 inches first hole Hole Thread Diameter: 0.3125 inches Primary Washer Outside Diameter: Between 0.625 inches and 0.635 inches Primary Washer Style: Flat Primary Washer Material Thickness: Between 0.503 inches and 0.508 inches
0.380 inches first hole Hole Thread Diameter: 0.3125 inches Primary Washer Outside Diameter: Between 0.625 inches and 0.635 inches Primary Washer Style: Flat Primary Washer Material Thickness: Between 0.503 inches and 0.508 inches Material:
0.380 inches first hole Hole Thread Diameter: 0.3125 inches Primary Washer Outside Diameter: Between 0.625 inches and 0.635 inches Primary Washer Style: Flat Primary Washer Material Thickness: Between 0.503 inches and 0.508 inches Material: Steel comp 303 stand-off or steel comp 304 stand-off

Passivate

## NSN 5306-01-552-6099

Assembled Washer Bolt - Page 2 of 2



Surface Treatment Specification:

Astma967 assn standard single treatment response

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0