NSN 5306-01-560-7687

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-560-7687

Thread Oleges
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.173 inches
Fastener Length:
5.938 inches
Head Style:
Spline extended washer
Head Height:
0.600 inches
Extended Washer Diameter:
1.394 inches
Extended Washer Thickness:
0.118 inches
Grip Diameter:
Between 0.748 inches and 0.749 inches
Head Minor Diameter:
Between 0.797 inches and 0.812 inches
Thread Diameter:
0.750 inches
Grip Length:
Between 4.740 inches and 4.760 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Surface Finish:
32.0 microinches head
Product Name:
Bolt tension steel 220ksi ftu 450 degrees f external wrenching spline drive flanged head
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:

Mil-c-8837 type 2 class 3 military specification single treatment response

NSN 5306-01-560-7687

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Specification Data:
Nas-21297 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-c-8837 spec.