

View Online at <https://aerobasegroup.com/nsn/5306-01-560-8002>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.475 inches

Fastener Length:

Between 2.297 inches and 2.327 inches

Head Style:

Bevel-conical

Head Diameter:

Between 0.428 inches and 0.438 inches

Head Height:

0.250 inches

Hole Diameter:

Between 0.037 inches and 0.042 inches

Internal Drive Style:

Hexagon

End Application:

Spec item

Thread Diameter:

0.248 inches

Width Across Flats:

Between 0.188 inches and 0.190 inches

Hole Quantity:

2

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

34.0 rockwell c and 40.0 rockwell c

Thread Pitch In Millimeters:

1.0

Hole Configuration Style:

Round internal hexagon

Product Name:

Bolts internal wrenching 160 ksi ftu and 96 ksi fsu

Material:

Steel comp 4340 and steel comp 4140 and steel comp 8740 and steel comp 8735 and steel comp 4340h and steel comp 4140

Material Specification:

Nas-20004 national std/spec single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type 2 class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

Nas-20004 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0