## NSN 5306-01-566-1855

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-566-1855 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.697 inches **Fastener Length:** Between 4.182 inches and 4.212 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 1.145 inches and 1.165 inches Width Between Flats: 1.519 inches **Extended Washer Diameter:** Between 2.115 inches and 2.125 inches **Extended Washer Thickness:** Between 0.259 inches and 0.279 inches **Grip Diameter:** Between 1.248 inches and 1.249 inches **Thread Diameter:** 1.250 inches **Grip Length:** Between 2.490 inches and 2.510 inches Thready Qty Per Inch (tpi): 12 Min. Tensile Strength (psi): 202500 pounds per square inch **Special Features:** Double shear 265, 100 poinds min Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Ams 6322 assn standard single material response or ams 6415 assn standard single material response or ams 6484 assn standard single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** 

N/a

Unjf

Shelf Life:

## NSN 5306-01-566-1855

Shear Bolt - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.