NSN 5306-01-569-9303

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-569-9303

т	Thread Class:
3	a
-	- Thread Direction:
R	Right-hand
	Thread Length:
	.614 inches
F	astener Length:
	.102 inches
Н	lead Style:
D	Double hexagon w/hole
Н	lead Height:
0	.388 inches
V	Vidth Between Flats:
0	.490 inches
E	Extended Washer Diameter:
0	.644 inches
E	Extended Washer Thickness:
0	.091 inches
Н	lole Diameter:
0	.055 inches
G	Grip Diameter:
0	.374 inches
E	and Application:
Ν	limrod 2000
Т	hread Diameter:
0	.375 inches
G	Grip Length:
1	.488 inches
Н	lole Quantity:
4	
Н	lole Type:
D	Drilled
Т	hready Qty Per Inch (tpi):
2	4
N	/lin. Tensile Strength (psi):
1	0870 pounds per square inch
Н	lole Configuration Style:
F	lexagon longitudinal hole
Ρ	Product Name:
С	Close tolerance bolt
S	Special Features:
B	Bolt-close tolerance, 12 point, flange head, 220 ksi ftu, cres; for use in

Bolt-close tolerance, 12 point, flange head, 220 ksi ftu, cres; for use in titanium structures intended for use with st3m572 nut

NSN 5306-01-569-9303

Close Tolerance Bolt - Page 2 of 2



Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard 1st material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams-qq-p-35 assn standard 1st treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0