

View Online at <https://aerobasegroup.com/nsn/5306-01-570-1474>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.551 inches

Fastener Length:

2.015 inches

Head Style:

Double hexagon extended washer

Head Height:

0.348 inches

Width Between Flats:

0.420 inches

Extended Washer Diameter:

0.526 inches

Extended Washer Thickness:

0.082 inches

Grip Diameter:

0.312 inches

Shank Unthreaded Hole Diameter:

0.076 inches grip and 0.081 inches grip

End Application:

Nimrod 2000

Thread Diameter:

0.312 inches

Grip Length:

1.116 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

7020 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.459 inches grip and 1.469 inches grip

Product Name:

Close tolerance bolt

Special Features:

Bolt-close tolerance, 12 point, flange head, 220 ksi ftu, cres; drilled shank

Material:

Steel comp xm-13

Material Specification:

Ams-5629 assn standard 1st material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams-qq-p-35 assn standard 1st treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A003b0