

View Online at <https://aerobasegroup.com/nsn/5306-01-570-7381>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.594 inches

Fastener Length:

Between 2.204 inches and 2.234 inches

Head Style:

Dished hexagon

Head Height:

Between 0.219 inches and 0.234 inches

Width Between Flats:

Between 0.679 inches and 0.690 inches

Grip Diameter:

Between 0.436 inches and 0.437 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.437 inches

Grip Length:

Between 1.615 inches and 1.635 inches

Thread Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.018 inches first hole

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Ams 6415 assn standard 1st material response or ams 6322 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A003b0