NSN 5306-01-571-6194

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-571-6194

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.425 inches |
| Fastener Length: |
| Between 3.035 inches and 3.065 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.125 inches and 0.140 inches |
| Width Between Flats: |
| Between 0.429 inches and 0.439 inches |
| Grip Diameter: |
| Between 0.249 inches and 0.250 inches |
| Shank Unthreaded Hole Diameter: |
| 0.076 inches first hole |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 2.615 inches and 2.635 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 2.872 inches first hole |
| Product Name: |
| Bolt hex head close tolerance a286 cres long threads self locking and non locking |
| Color: |
| Green threads |
| Material: |
| Iron alloy 660 |
| Surface Treatment: |
| Cadmium and chromate |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5306-01-571-6194

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0