## NSN 5306-01-572-8984



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-572-8984 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.338 inches **Fastener Length:** Between 0.515 inches and 0.535 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.339 inches and 0.381 inches **Grip Diameter:** Between 0.188 inches and 0.189 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.177 inches and 0.197 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degree flush head 160, 000 psi uts Material: Steel comp 4140 and steel comp 4340 and steel comp 8740 **Material Specification:** Mil-s-5626 military specification single material response and ams6415 assn standard 2nd material response and mil-s-60494 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, ty ii. Cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5306-01-572-8984

Shear Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.