

View Online at <https://aerobasegroup.com/nsn/5306-01-575-9057>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.338 inches

**Fastener Length:**

Between 0.885 inches and 0.915 inches

**Head Style:**

Fillister countersunk

**Head Diameter:**

Between 0.339 inches and 0.381 inches

**Head Height:**

0.083 inches

**Grip Diameter:**

0.189 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.547 inches and 0.577 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or ams 6415 assn standard 2nd material response or mil-s-6049 military specification 3rd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, ty ii, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.