

View Online at <https://aerobasegroup.com/nsn/5306-01-576-3743>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.578 inches

**Fastener Length:**

Between 3.313 inches and 3.343 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.173 inches and 0.203 inches

**Width Between Flats:**

0.554 mils and 0.564 centimeters

**Grip Diameter:**

0.374 mils and 0.375 centimeters

**Shank Unthreaded Hole Diameter:**

0.106 mils and 0.116 centimeters

**Thread Diameter:**

0.375 inches

**Grip Length:**

2.740 mils and 2.760 centimeters

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.131 inches

**Product Name:**

Bolt, tension, hex head, close tolerance, alloy steel, long thread, reduced major dia, nonlocking, 160 ksi ftu

**Material:**

Steel comp 4140 or steel comp 4340

**Material Specification:**

Ams6349 assn standard single material response or ams6340 assn standard single material response or ams 6415 assn standard single material response or ams 6484 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams-qq-p-416 type ii class 2 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0