NSN 5306-01-576-4072

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-576-4072 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** Between 1.516 inches and 1.546 inches **Head Height:** Between 0.141 inches and 0.171 inches Width Between Flats: 0.492 mils and 0.502 centimeters **Grip Diameter:** 0.311 mils and 0.312 centimeters **Shank Unthreaded Hole Diameter:** 0.066 mils and 0.086 centimeters **Thread Diameter:** 0.313 inches **Grip Length:** 1.052 mils and 1.072 centimeters Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 1.351 inches **Product Name:** Bolt, tension, hex head, close tolerance, 6al-4v titanium alloy, long thread, reduced major thread dia, nonlocking, 160 ksiftu Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Nas4006 national std/spec single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5306-01-576-4072

Shear Bolt - Page 2 of 2



Fiig:

A003b0