

View Online at <https://aerobasegroup.com/nsn/5306-01-579-3983>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.425 inches

Fastener Length:

Between 3.785 inches and 3.815 inches

Head Style:

Dished hexagon

Head Height:

Between 0.125 inches and 0.140 inches

Width Between Flats:

Between 0.429 inches and 0.439 inches

Grip Diameter:

Between 0.249 inches and 0.250 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 3.650 inches and 3.850 inches

Thread Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Product Name:

Bolt, tension, hex head, close tolerance, a286 cres, long thread, reduced major thread dia., nonlocking, 160 ksi ftu

Special Features:

Has drilled shank, 0.046 in, dia. Hole centered 0.178 in. From screw end

Material:

Stainless steel

Material Specification:

Uns662286 iaw ams5731, ams5732, ams 5737 or ams5835 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams2700, method 1, type 2 or type 8, class assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0