## NSN 5306-01-580-6082

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-580-6082

view Offilitie at https://aerobasegroup.com/nsn/3300-01-300-0002
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.728 inches and 0.738 inches
Fastener Length:
Between 2.771 inches and 2.821 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.420 inches and 0.440 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Extended Washer Diameter:
Between 0.723 inches and 0.743 inches
Extended Washer Thickness:
Between 0.099 inches and 0.109 inches
Grip Diameter:
Between 0.4672 inches and 0.4682 inches
Thread Diameter:
0.4375 inches
Grip Length:
Between 1.678 inches and 1.698 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
200000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Stainless steel
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment Specification:
Bms10-85, type 1, class b assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5306-01-580-6082

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0