

View Online at <https://aerobasegroup.com/nsn/5306-01-580-6083>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.728 inches and 0.738 inches

Fastener Length:

Between 2.583 inches and 2.633 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.420 inches and 0.440 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Extended Washer Diameter:

Between 0.723 inches and 0.743 inches

Extended Washer Thickness:

Between 0.099 inches and 0.109 inches

Grip Diameter:

Between 0.4672 inches and 0.4682 inches

Thread Diameter:

0.4375 inches

Grip Length:

Between 1.490 inches and 1.510 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

200000 pounds per square inch

Surface Finish:

32.0 microinches threads

Material:

Stainless steel

Material Specification:

Ams 5737 assn standard single material response

Surface Treatment Specification:

Bms10-85, type 1, class b assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A003b0