
## NSN 5306-01-580-6092

Shear Bolt - Page 1 of 2





## Thread Class: 3a

Thread Direction:

Right-hand

#### Thread Length:

Between 0.728 inches and 0.738 inches

#### Fastener Length:

Between 2.521 inches and 2.571 inches

#### Head Style:

Double hexagon w/hole

#### Head Height:

Between 0.420 inches and 0.440 inches

#### Width Between Flats:

Between 0.492 inches and 0.502 inches

#### **Extended Washer Diameter:**

Between 0.723 inches and 0.743 inches

#### **Extended Washer Thickness:**

Between 0.099 inches and 0.109 inches

#### Grip Diameter:

Between 0.4672 inches and 0.4682 inches

### Thread Diameter:

0.4375 inches

Grip Length:

Between 1.428 inches and 1.448 inches

## Thready Qty Per Inch (tpi):

20

## Min. Tensile Strength (psi):

200000 pounds per square inch

#### Surface Finish:

32.0 microinches threads

#### Material:

Stainless steel

## Material Specification:

Ams 5737 assn standard single material response

## Surface Treatment Specification:

Bms10-85, type 1, class b assn standard single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

Unit Of Measure:

# NSN 5306-01-580-6092

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

