NSN 5306-01-580-6095

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-580-6095 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.808 inches and 0.818 inches **Fastener Length:** Between 3.468 inches and 3.518 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.420 inches and 0.440 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** Between 0.113 inches and 0.133 inches **Grip Diameter:** Between 0.5297 inches and 0.5307 inches **Thread Diameter:** 0.5000 inches **Grip Length:** Between 2.240 inches and 2.260 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 200000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Stainless steel **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment Specification:** Bms10-85, type 1, class b assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5306-01-580-6095

Shear Bolt - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A003b0