

View Online at <https://aerobasegroup.com/nsn/5306-01-580-6099>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.638 inches and 0.648 inches

**Fastener Length:**

Between 2.333 inches and 2.383 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.330 inches and 0.350 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Extended Washer Diameter:**

Between 0.639 inches and 0.649 inches

**Extended Washer Thickness:**

Between 0.081 inches and 0.101 inches

**Grip Diameter:**

Between 0.3896 inches and 0.3901 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.678 inches and 1.698 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

200000 pounds per square inch

**Surface Finish:**

32.0 microinches threads

**Material:**

Stainless steel

**Material Specification:**

Ams 5737 assn standard single material response

**Surface Treatment Specification:**

Bms10-85, type 1, class b assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A003b0