NSN 5306-01-580-6099

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-580-6099 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.638 inches and 0.648 inches **Fastener Length:** Between 2.333 inches and 2.383 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.330 inches and 0.350 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Extended Washer Diameter:** Between 0.639 inches and 0.649 inches **Extended Washer Thickness:** Between 0.081 inches and 0.101 inches **Grip Diameter:** Between 0.3896 inches and 0.3901 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.678 inches and 1.698 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 200000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Stainless steel **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment Specification:** Bms10-85, type 1, class b assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5306-01-580-6099

Shear Bolt - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A003b0