## NSN 5306-01-580-6103

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-580-6103

View Online at https://aerobasegroup.com/nsn/5306-01-580-6103
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.638 inches and 0.648 inches
Fastener Length:
Between 1.958 inches and 2.008 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.330 inches and 0.350 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
Between 0.081 inches and 0.101 inches
Grip Diameter:
Between 0.3896 inches and 0.3901 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.678 inches and 1.698 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
200000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Stainless steel
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Ams 2700, type 2 assn standard single treatment response or ams 2700, type 8 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5306-01-580-6103

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

Yes - demil/mli

Fiig:

A003b0