
NSN 5306-01-580-6322

Shear Bolt - Page 1 of 2



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.384 inches and 0.394 inches

Fastener Length:

Between 1.187 inches and 1.232 inches

Head Style:

Dished hexagon

Head Height:

Between 0.125 inches and 0.140 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Grip Diameter:

Between 0.248 inches and 0.249 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 0.678 inches and 0.698 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

95000 pounds per square inch

Surface Finish:

63.0 microinches bearing surface of head

Material:

Titanium alloy

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Bms10-85, type 1, class a assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli



NSN 5306-01-580-6322

Shear Bolt - Page 2 of 2

Fiig: A003b0

