
# NSN 5306-01-580-6473

Shear Bolt - Page 1 of 2





# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.449 inches and 0.459 inches

#### Fastener Length:

Between 1.345 inches and 1.390 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.156 inches and 0.171 inches

#### Width Between Flats:

Between 0.492 inches and 0.502 inches

#### Grip Diameter:

Between 0.310 inches and 0.312 inches

# **Thread Diameter:**

0.312 inches

# Grip Length:

Between 0.740 inches and 0.760 inches

# Thready Qty Per Inch (tpi):

24

# Min. Tensile Strength (psi):

95000 pounds per square inch

#### Surface Finish:

63.0 microinches bearing surface of head

# Material:

Titanium alloy

# **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

# Surface Treatment Specification:

Bms10-85, type 1, class a assn standard single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# NSN 5306-01-580-6473

Shear Bolt - Page 2 of 2

Fiig: A003b0

