NSN 5306-01-580-6522



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-580-6522 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.449 inches and 0.459 inches **Fastener Length:** Between 2.095 inches and 2.140 inches **Head Style:** Dished hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Grip Diameter:** Between 0.310 inches and 0.312 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.490 inches and 1.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 95000 pounds per square inch **Surface Finish:** 63.0 microinches bearing surface of head Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum

Surrace Finish:

63.0 microinches bearing surface of head

Material:

Titanium alloy

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn

Surface Treatment:

Aluminum

Surface Treatment Specification:

Bms10-85, type 1, class a assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization: Yes - demil/mli

NSN 5306-01-580-6522

Shear Bolt - Page 2 of 2



Fiig:

A003b0