

View Online at <https://aerobasegroup.com/nsn/5306-01-581-0094>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.578 inches

Fastener Length:

4.203 inches

Head Style:

Hexagon

Head Height:

0.188 inches

Width Between Flats:

Between 0.554 inches and 0.564 inches

Hole Diameter:

0.106 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.106 inches

Thread Diameter:

0.375 inches

Grip Length:

3.625 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Round

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.006 inches

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Ams 6349 assn standard single material response or ams 6382 assn standard single material response or ams 6415 assn standard single material response or ams 6484 assn standard single material response or ams 6322 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0