NSN 5306-01-581-3421

Machine Bolt - Page 1 of 2

Thread Class:

Thread Direction:

За

Unjf



View Online at https://aerobasegroup.com/nsn/5306-01-581-3421

| Right-hand |
|--|
| Thread Length: |
| 0.450 inches |
| Fastener Length: |
| 3.425 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| 0.178 inches |
| Width Between Flats: |
| Between 0.429 inches and 0.439 inches |
| Hole Diameter: |
| 0.046 inches |
| Grip Diameter: |
| Between 0.2485 inches and 0.2495 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| 3.000 inches |
| Hole Quantity: |
| 3 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 16000 pounds per square inch |
| Hole Configuration Style: |
| Round |
| Material: |
| Steel comp 4140 or steel comp 4340 or steel comp 8740 |
| Material Specification: |
| Ams6359 assn standard single material response or ams6382 assn standard single material response or ams6415 assn standard single |
| material response or ams6484 assn standard single material response or ams6322 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type ii, class 2 federal specification single treatment response |
| Thread Series Designator: |

NSN 5306-01-581-3421

Machine Bolt - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0