## NSN 5306-01-581-5618

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-581-5618 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.420 inches and 0.430 inches **Fastener Length:** Between 2.660 inches and 2.715 inches **Head Style:** Dished hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 2.115 inches and 2.135 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads **Product Name:** Bolt, hex head, 160 ksi min tensile, long thread, a286, nonlocking, Material: Stainless steel **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Amsqq-p-416, type 2, cl 2 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a **Unit Of Measure:** 

## NSN 5306-01-581-5618

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0