# NSN 5306-01-581-5663

Shear Bolt - Page 1 of 2





# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.420 inches and 0.430 inches

#### Fastener Length:

Between 1.097 inches and 1.152 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.125 inches and 0.140 inches

#### Width Between Flats:

Between 0.430 inches and 0.439 inches

#### Grip Diameter:

Between 0.2490 inches and 0.2495 inches

#### **Thread Diameter:**

0.250 inches

# Grip Length:

Between 0.552 inches and 0.572 inches

## Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Surface Finish:

32.0 microinches threads

#### **Product Name:**

Bolt, hex head, 160 ksi min tensile, long thread, a286, nonlocking,

#### Material:

Stainless steel

## **Material Specification:**

Ams 5737 assn standard single material response

#### Surface Treatment:

Cadmium

## Surface Treatment Specification:

Amsqq-p-416, type 2, cl 2 assn standard single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5306-01-581-5663

Shear Bolt - Page 2 of 2

# Demilitarization:

Yes - demil/mli

Fiig:

A003b0

