## NSN 5306-01-581-5698

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-581-5698 **Thread Class:** 

За

**Thread Direction:** 

Right-hand

Thread Length:

Between 0.420 inches and 0.430 inches

**Fastener Length:** 

Between 2.285 inches and 2.330 inches

**Head Style:** 

Dished hexagon

**Head Height:** 

Between 0.125 inches and 0.140 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

**Grip Diameter:** 

Between 0.2490 inches and 0.2495 inches

**Thread Diameter:** 

0.250 inches

**Grip Length:** 

Between 1.740 inches and 1.760 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

**Surface Finish:** 

32.0 microinches threads

**Product Name:** 

Bolt, hex head, 160 ksi min tensile, long thread, a286, nonlocking,

**Special Features:** 

Drilled shank centered at position approximately 0.178 inches from threaded end

Material:

Stainless steel

**Material Specification:** 

Ams 5737 assn standard single material response

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Amsqq-p-416, type 2, cl 2 assn standard single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5306-01-581-5698

Shear Bolt - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A003b0