NSN 5306-01-581-5704

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-581-5704

view Offinite at https://aerobasegroup.com/hsh/3500-01-501-5704
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.420 inches and 0.430 inches
Fastener Length:
Between 1.097 inches and 1.152 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.552 inches and 0.572 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Product Name:
Bolt, hex head, 160 ksi min tensile, long thread, a286, nonlocking,
Special Features:
Drilled shank centered at position approximately 0.178 inches from threaded end
Material:
Stainless steel
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Amsqq-p-416, type 2, cl 2 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-01-581-5704

Shear Bolt - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A003b0