## NSN 5306-01-581-5713

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-581-5713

view eximite at https://acrossacogreep.com/non/pocco 0.1 co.1 co.1 co.1 co.1 co.1 co.1 co.1 co
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.420 inches and 0.430 inches
Fastener Length:
Between 0.910 inches and 0.955 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.365 inches and 0.385 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Product Name:
Bolt, hex head, 160 ksi min tensile, long thread, a286, nonlocking,
Special Features:
Drilled head in 3 places centered on alternating flats, having diameter of 0.046 inches
Material:
Stainless steel
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Amsqq-p-416, type 2, cl 2 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5306-01-581-5713

Shear Bolt - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0