## NSN 5306-01-581-6147

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-581-6147 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.340 inches and 0.350 inches **Fastener Length:** Between 2.022 inches and 2.072 inches **Head Style:** Double hexagon **Head Height:** Between 0.130 inches and 0.150 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.1879 inches and 0.1895 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.552 inches and 1.572 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 110000 pounds per square inch **Surface Finish:** 32.0 microinches threads **Product Name:** Bolt, 12 point head, short thread, close tol, a286 cres, 110 ksi min shear **Special Features:** Drilled shank having hole diameter of 0.070 inches centered approximatly 0.117 inches from threaded end Material: Stainless steel **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams qq-p-416, type 2, cl 2 assn standard single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

## NSN 5306-01-581-6147

Close Tolerance Bolt - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0