

View Online at <https://aerobasegroup.com/nsn/5306-01-581-6158>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.340 inches and 0.350 inches

**Fastener Length:**

Between 1.960 inches and 2.010 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.130 inches and 0.150 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Grip Diameter:**

Between 0.1879 inches and 0.1895 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 1.490 inches and 1.510 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

110000 pounds per square inch

**Surface Finish:**

32.0 microinches threads

**Product Name:**

Bolt, 12 point head, short thread, close tol, a286 cres, 110 ksi min shear

**Special Features:**

Drilled shank having hole diameter of 0.070 inches centered approximately 0.117 inches from threaded end

**Material:**

Stainless steel

**Material Specification:**

Ams 5737 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams qq-p-416, type 2, cl 2 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0