## NSN 5306-01-581-6162

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-581-6162

3
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.384 inches and 0.394 inches
Fastener Length:
Between 2.278 inches and 2.328 inches
Head Style:
Double hexagon
Head Height:
Between 0.154 inches and 0.174 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Grip Diameter:
Between 0.2479 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 1.740 inches and 1.760 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
110000 pounds per square inch
Surface Finish:
32.0 microinches threads
Product Name:
Bolt, 12 point head, short thread, close tol, a286 cres, 110 ksi min shear
Special Features:
Drilled shank having hole diameter of 0.070 inches centered approximatly 0, 117 inches from threaded end
Material:
Stainless steel
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Ams qq-p-416, type 2, cl 2 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:

N/a

## NSN 5306-01-581-6162

Close Tolerance Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0