## NSN 5306-01-581-6168

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-581-6168 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.465 inches and 0.475 inches **Fastener Length:** Between 2.770 inches and 2.820 inches **Head Style:** Double hexagon **Head Height:** Between 0.200 inches and 0.220 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Grip Diameter:** Between 0.3731 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 2.115 inches and 2.135 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 110000 pounds per square inch **Surface Finish:** 32.0 microinches threads **Product Name:** Bolt, 12 point head, short thread, close tol, a286 cres, 110 ksi min shear **Special Features:** Drilled shank having hole diameter of 0.070 inches centered approximatly 0.117 inches from threaded end Material: Stainless steel **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Bms 10-85, type 1, cl a assn standard single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

## NSN 5306-01-581-6168

Close Tolerance Bolt - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0