

View Online at <https://aerobasegroup.com/nsn/5306-01-581-6197>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.384 inches and 0.394 inches

**Fastener Length:**

Between 3.249 inches and 3.294 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2479 inches and 0.2495 inches

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 2.740 inches and 2.760 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Surface Finish:**

32.0 microinches threads

**Product Name:**

Bolt, hex head, 95 ksi shear, short thread, a286, nonlocking

**Material:**

Stainless steel

**Material Specification:**

Ams 5737 assn standard single material response or ams 5853 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Amsqq-p-416, type 2, cl 2 plus bps-f-69 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0