## NSN 5306-01-581-6213



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-581-6213 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.449 inches and 0.459 inches **Fastener Length:** Between 0.687 inches and 0.732 inches **Head Style:** Dished hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Grip Diameter:** Between 0.3260 inches and 0.3276 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 95000 pounds per square inch **Surface Finish:** 32.0 microinches threads **Product Name:** Bolt, hex head, 95 ksi shear, short thread, a286, nonlocking Material: Stainless steel **Material Specification:** Ams 5737 assn standard single material response or ams 5853 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** 

Amsqq-p-416, type 2, cl 2 plus bps-f-69 assn standard single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5306-01-581-6213

Shear Bolt - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A003b0