# NSN 5306-01-581-6502

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-581-6502



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.384 inches and 0.394 inches

#### Fastener Length:

Between 1.499 inches and 1.544 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.125 inches and 0.140 inches

#### Width Between Flats:

Between 0.430 inches and 0.439 inches

#### Grip Diameter:

Between 0.2481 inches and 0.2495 inches

#### **Thread Diameter:**

0.250 inches

# Grip Length:

Between 0.990 inches and 1.010 inches

# Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

95000 pounds per square inch

#### Surface Finish:

32.0 microinches threads

#### **Product Name:**

Bolt, hex head, 95 ksi shear, short thread, a286, self-locking

#### **Special Features:**

Has patch locking device

#### Material:

Stainless steel

## Material Specification:

Ams 5737 assn standard single material response or ams 5853 assn standard single material response

#### Surface Treatment:

Aluminum

# Surface Treatment Specification:

Bms10-85, type 1, class a assn standard single treatment response

# Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5306-01-581-6502

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

