NSN 5306-01-581-6505

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-581-6505

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.384 inches and 0.394 inches
Fastener Length:
Between 2.811 inches and 2.856 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Grip Diameter:
Between 0.2481 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 2.302 inches and 2.322 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
95000 pounds per square inch
Surface Finish:
32.0 microinches threads
Product Name:
Bolt, hex head, 95 ksi shear, short thread, a286, self-locking
Special Features:
Has patch locking device
Material:
Stainless steel
Material Specification:
Ams 5737 assn standard single material response or ams 5853 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Bms10-85, type 1, class a assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-01-581-6505

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0