NSN 5306-01-581-6512

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-581-6512

View Online at https://aerobasegroup.com/nsn/5306-01-581-6512
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.465 inches and 0.475 inches
Fastener Length:
Between 2.518 inches and 2.563 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.865 inches and 1.885 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
95000 pounds per square inch
Surface Finish:
32.0 microinches threads
Product Name:
Bolt, hex head, 95 ksi shear, short thread, a286, nonlocking
Special Features:
Drilled shank with hole diameter of 0.106 inches centered 0.216 inches from threaded end
Material:
Stainless steel
Material Specification:
Ams 5737 assn standard single material response or ams 5853 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Ams 2700, type 2 assn standard single treatment response or ams 2700, type 8 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-01-581-6512

Shear Bolt - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0