

View Online at <https://aerobasegroup.com/nsn/5306-01-585-5660>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.345 inches

**Fastener Length:**

Between 1.642 inches and 1.672 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.110 inches and 0.125 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Grip Diameter:**

Between 0.188 inches and 0.189 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 1.302 inches and 1.322 inches

**Thread Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.681 inches first hole

**Product Name:**

Bolt tension hex head close tolerance

**Special Features:**

Item has drilled shank bolt

**Material:**

Stainless steel

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0