NSN 5306-01-585-5660



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-585-5660 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.345 inches **Fastener Length:** Between 1.642 inches and 1.672 inches **Head Style:** Dished hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.188 inches and 0.189 inches **Shank Unthreaded Hole Diameter:** 0.070 inches first hole **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.302 inches and 1.322 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 95000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 2.681 inches first hole **Product Name:** Bolt tension hex head close tolerance **Special Features:** Item has drilled shank bolt Material: Stainless steel **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5306-01-585-5660

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0