NSN 5306-01-585-6816

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-585-6816

view Offilite at https://aerobasegroup.com/hsi//5500-01-505-0010
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.241 inches and 0.244 inches
Fastener Length:
Between 1.793 inches and 1.823 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Hole Diameter:
0.046 inches
Grip Diameter:
Between 0.249 inches and 0.250 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 1.428 inches and 1.448 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Product Name:
Bolt, tension, hex head, close tolerance, a286 cres, short thread, reduced major thread dia, 160 ksi ftu
Color:
Green threads
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
material response, or ams 5853 assn standard single material response

Cadmium

Surface Treatment:

NSN 5306-01-585-6816

Shear Bolt - Page 2 of 2



Ams-qq-p-416, type ii, class 2 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0