

View Online at <https://aerobasegroup.com/nsn/5306-01-585-9653>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.370 inches

**Fastener Length:**

1.308 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.429 inches and 0.439 inches

**Grip Diameter:**

0.248 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches bearing surface of head and 0.086 inches bearing surface of head

**Thread Diameter:**

0.250 inches

**Grip Length:**

0.938 inches

**Thread Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.050 inches grip and 1.100 inches grip

**Surface Finish:**

32.0 microinches bearing surface of head

**Material:**

Titanium alloy uns r56400

**Surface Treatment:**

Anodize

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6404 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0