

View Online at <https://aerobasegroup.com/nsn/5306-01-587-7153>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.345 inches

Fastener Length:

2.128 inches

Head Style:

Dished hexagon

Head Height:

Between 0.110 inches and 0.125 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Grip Diameter:

Between 0.188 inches and 0.189 inches

Shank Unthreaded Hole Diameter:

0.070 inches first shoulder and 0.080 inches first shoulder

Thread Diameter:

0.190 inches

Grip Length:

Between 1.428 inches and 1.448 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.064 inches first shoulder

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5732 assn standard single material response and ams 5737 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams qq-p-416, ty ii, cl2 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0