

View Online at <https://aerobasegroup.com/nsn/5306-01-588-1845>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.567 inches and 0.582 inches

**Fastener Length:**

Between 0.539 inches and 0.579 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.110 inches and 0.125 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Shoulder Diameter:**

0.190 inches first shoulder

**Shoulder Length:**

0.567 inches and 0.582 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

2350 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.386 inches first hole

**Shoulder Shape:**

Round first shoulder

**Product Name:**

Bolt, shoulder, hex head, close tolerance, cres-a286, 95 ksi fsu

**Material:**

Stainless steel

**Material Specification:**

A286 (uns s66286) conforming to ams5731, ams5732, ams5737, or ams5853 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams2700 method 1, type 2 or type 8, class 4 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0