

View Online at <https://aerobasegroup.com/nsn/5306-01-588-2505>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.529 inches and 0.554 inches

Fastener Length:

1.313 inches

Head Style:

Hexagon

Head Height:

Between 0.219 inches and 0.234 inches

Width Between Flats:

Between 0.678 inches and 0.690 inches

Shoulder Diameter:

1.323 inches first shoulder and 1.333 inches first shoulder

Shoulder Length:

0.499 inches first shoulder and 0.500 inches first shoulder

Shank Unthreaded Hole Diameter:

0.106 inches threads

Thread Diameter:

0.438 inches

Thready Qty Per Inch (tpi):

20

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.111 inches threads

Shoulder Shape:

Round first shoulder

Material:

Stainless steel

Material Specification:

A286 (uns s66286) per ams5731, ams5732, ams5737 or ams5853 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams2700, method 1, type 2 or type 8, class 4 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0