## NSN 5306-01-588-5206

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-588-5206 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.735 inches **Fastener Length:** Between 4.485 inches and 4.500 inches **Head Style:** Dished hexagon **Head Height:** Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches **Grip Diameter:** 0.510 inches **Thread Diameter:** 0.500 inches **Grip Length:** 3.750 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Product Name:** Bolt, tension, hexz head, close tolerance, alloy steel, long thread, reduced major diameter, self-locking, 160 ksi ftu Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams-qq-p-416, type ii, class 2 assn standard single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6608 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5306-01-588-5206

Shear Bolt - Page 2 of 2



Fiig:

A003b0